

# GRAND ARC 320 CEL PFC MV



## ACCESSORI CONSIGLIATI

1. CAVO PORTA ELETTRODO 35MM2 4MT	21004
2. CAVO MASSA 35MM2 3MT	21005
3. TORCIA TIG LKM 26V 4MT	22020
4. MASCHERA LKM BASE H	31000
5. WIRELESS REMOTE CONTROL FOR MMA	43008



## DATI TECNICI

CODICE	11003
TENSIONE DI ALIMENTAZIONE	110V-460V
FREQUENZA DI RETE	50/60 HZ
FASI	1-3
POTENZA MAX ASSORBITA*	6,8KW-8,2KW (1PH-110V) 6,6KW-7,0KW (1PH-230V) 9,0KW-9,0KW (3PH-230V) 9,2KW-11,8KW (3PH-400V)
CORRENTE ASSORBITA MAX (I1 MAX)*	30A-36A (1PH-110V) 29A-31A (1PH-230V) 24A-24A (3PH-230V) 14A-18A (3PH-400V)
CORRENTE ASSORBITA EFFICACE (I1 EFF)*	23A-20A-(1PH-110V) 21A-21A-(1PH-230V) 15A-14A-(3PH-230V) 12A-9A-(3PH-400V)
CICLO DI LAVORO 40% (10 MIN 40°C)*	315A (MMA 3PH-400V)
CICLO DI LAVORO 60% (10 MIN 40°C)*	150A-85A (1PH-110V) 230A-175A (1PH-230V) 245A-195A (3PH-230V) 260A-260A (3PH-400V)
CICLO DI LAVORO 100% (10 MIN 40°C)*	120A-70A (1PH-110V) 180A-135A (1PH-230V) 190A-150A (3PH-230V) 200A-200A (3PH-400V)
TENSIONE A VUOTO	80V
RANGE CORRENTE SALDATURA*	10A/150A 10A/120A (1PH-110V) 10A/250A 10A/200A (1PH-220V) 10A/315A 10A/250A (3PH-220V) 10A/315A 10A/315A (3PH-400V)
PESO	20KG
DIMENSIONI	580X240X425mm
GRADO DI PROTEZIONE	IP23
CLASSE DI ISOLAMENTO	H
COS Ø	0,99 (1PH); 0,95(3PH)

\* (TIG/MMA)

