

GRAND PIPE 270 MULTI



ACCESSORI CONSIGLIATI

1. CAVO PORTA ELETTRODO 35MM2 4MT	21004
2. CAVO MASSA 35MM2 3MT	21005
3. MASCHERA LKM ALTAVISTA HD	33000
4. TORCIA TIG LKM STYLE 26 4MT	22014
5. MINI COOLER 220V	43004
6. MINI COOLER 400V	43005
7. LKM TROLLEY 2 RUOTE	40006
8. TORCIA TIG LKM STYLE 18 HC 4MT	22016
9. PEDALE CON CAVO 5MT	40010
10. COMANDO REMOTO DC WIRELESS	43000



DATI TECNICI

CODICE	12006
TENSIONE DI ALIMENTAZIONE	110V-460V
FREQUENZA DI RETE	50/60 HZ
FASI	1-3
POTENZA MAX ASSORBITA*	3,2KW-3,8KW (1PH-110V) 6,3KW-6,8KW (1PH-230V) 7,5KW-9,5KW (3PH-230V) 7,5KW-10,2KW (3PH-400V)
CORRENTE ASSORBITA MAX (I1 MAX)*	30A-35A (1PH-110V) 28A-30A (1PH-230V) 19A-24A (3PH-230V) 11A-15A (3PH-400V)
CORRENTE ASSORBITA EFFICACE (I1 EFF)*	19A-19A (1PH-110V) 15A-17A (1PH-230V) 12A-13A (3PH-230V) 7A-10A (3PH-400V)
CICLO DI LAVORO 40% (10 MIN 40°C)*	150A-120A 30% (1PH-110V) 250A-200A 30% (1PH-230V) 270A-250A 30% (3PH-230V) 270A-270A (3PH-400V)
CICLO DI LAVORO 60% (10 MIN 40°C)*	125A-85A (1PH-110V) 180A-145A (1PH-230V) 225A-180A (3PH-230V) 225A-225A (3PH-400V)
CICLO DI LAVORO 100% (10 MIN 40°C)*	95A-70A (1PH-110V) 140A-110A (1PH-230V) 175A-140A (3PH-230V) 175A-175A (3PH-400V)
TENSIONE A VUOTO	93V
RANGE CORRENTE SALDATURA*	10A/270A
PESO	22,5KG
DIMENSIONI	620X240X425MM
GRADO DI PROTEZIONE	IP23
CLASSE DI ISOLAMENTO	H
COS Ø	0,99
CONNETTORE TORCIA TIG	12 PINS

*(TIG/MMA)

